

Camlok®

LOW HEADROOM DRUM GRABS



DA/DAF DRUM GRAB

WLL 350 KG (PER PIECE)

EN- OPERATING MANUAL

(ALSO APPLICABLE FOR SPECIAL VERSIONS)

Columbus McKinnon Corporation Limited
Knutsford Way,
Sealand Industrial Estate,
Chester
CH1 4NZ
United Kingdom

CMCO
INTELLIGENT MOTION
Columbus McKinnon

Tel: +44 (0) 1244 375375

Email: sales.uk@cmco.eu

Web: www.cmco.com

Introduction

Products of Columbus McKinnon Corporation Limited have been built in accordance with the state-of-the-art and generally accepted engineering standards. Nonetheless, incorrect handling when using the products may cause dangers to life and limb of the user or third parties and/or damage to the hoist or other property.

The operating company is responsible for the proper and professional instruction of the operating personnel. For this purpose, all operators must read these operating instructions carefully prior to the initial operation.

These operating instructions are intended to acquaint the user with the product and enable him to use it to the full extent of its intended capabilities. The operating instructions contain important information on how to operate the product in a safe, correct and economic way. Acting in accordance with these instructions helps to avoid dangers, reduce repair costs and downtimes and to increase the reliability and lifetime of the product. The operating instructions must always be available at the place where the product is operated. Apart from the operating instructions and the accident prevention act valid for the respective country and area where the product is used, the commonly accepted regulations for safe and professional work must also be adhered to.

The personnel responsible for operation, maintenance or repair of the product must read, understand and follow these operating instructions.

The indicated protective measures will only provide the necessary safety, if the product is operated correctly and installed and/or maintained according to the instructions. The operating company is committed to ensure safe and trouble-free operation of the product.

DA/DAF Drum grab

Model	WLL	Jaw capacity diameter	Weight
	kg	mm	kg
DA	350	420-700	3.5
DAF	350	420-700	6

Table 1

General Safety

- ⚠ ALWAYS wear practical, protective clothing, gloves and footwear as a minimum.
- ⚠ ALWAYS bear in mind your safety and the safety of others while using this equipment.
- ⚠ DO NOT operate this equipment, if you feel ill, tired or are under the influence of alcohol or drugs.
- ⚠ This equipment MUST NOT be used to carry or lift personnel.

General Safety

ALWAYS check the operation of your Camlok lifting clamp before use.

ALWAYS place the palm of the hand on top of the load.

ALWAYS stand clear when lifting or lowering.

ALWAYS keep a record of inspections and repairs.

ALWAYS transport the load as close to the floor as possible.

NEVER use a worn or damaged Camlok lifting clamp.

NEVER lift more than one plate/product at a time.

NEVER leave a suspended load unattended or place a plate down on edge for a long period of time.

NEVER exceed the maximum working load limit

NEVER lower fast, **ALWAYS** lift and lower gently.

NEVER stand under a suspended load and if guiding a load by hand, **NEVER** grip the load with fingers on the underside.

NEVER pull or push the load where the crane cannot reach
NEVER force the locking lever.

Product Overview

The DA drum grab is designed for the vertical transportation of steel drums. The load lifting attachment is used for safely transporting single, upright barrels (according to EN ISO 15750-2) by means of an overhead crane within the jaw capacity indicated on the identity plate. The jaws grab under the lip of the drum with its form-fitting connection. The DAF drum grab works on the same principle as the DA grab. The model TR also offers the possibility of handling the load lifting attachment with a forklift truck.

Fitting:

- Check that the drum is free from grease, standing water, oil, scale and is not coated with paint or film.
- For transporting the drum vertical one clamps should be used.
- Check the weight of the clamp and ensure the lifting sling is slack.
- Lower the grab at least until the two textile belts are completely unloaded and the extending supporting tube rests on the cover of the barrel.
- While the two grab jaws are opened by lifting on the outer end, the supporting tube is adjusted to the diameter of the barrel by extending or retracting it.
- The grab jaws are then closed and ensure a positive connection together with the inner supporting tube and thus absolutely safe holding of the load.
- Take care not to damage the lifting surfaces.
- Check correct fitting and position before lifting.
- Check chain sling for twisting.

Lifting & Transport:

- Reposition the clamps if the drum tilts more than 5° to the side.
- Never exceed the maximum working load limit or pick up loads weighing less than the minimum working load limit as marked on each clamp.
- Check position and fitting of clamp as weight is applied
- Check for obstacles prior to lift. Lift slowly and smoothly at all times.
- Lifting slings must be vertical at all times.
- Always keep clear of the area below and surrounding the load while lifting and transporting as the plate may kick or swing as it lifts from the floor.
- Minimise the danger area by moving drums as close to the ground as possible.
- Take precautions to stop the drum from swinging.

Release:

- Place loads down gently. Fast lowering may release the clamp.
- To remove the clamp place the drum down on the floor and pull the clamps apart from the centre to open the jaw.
- The clamp should only be released when the entire load is removed.

Testing/Service:

All Camlok lifting clamps are tested before sale to a proof load of twice the working load limit. Any clamp that has been repaired must be tested.

Care and Maintenance:

The maintenance schedule is based on normal usage of clamps operating in a workshop environment. Maintenance frequency must be increased if clamps are subject to heavy usage or operated in adverse conditions.

Fasteners fitted to 'Camlok' clamps are retained with Loctite 270 Thread Locking Compound unless the bolt is secured with a nylon nut. DO NOT use any other grade. For maintenance, use heat to loosen locking compound (up to 80°). Always keep a record of inspections and repairs.

CHESTER OFFICE

Knutsford Way, Sealand Industrial Estate
Chester, CH1 4NZ
United Kingdom
Telephone: +44 (0) 1244 375375
Email: sales.uk@cmco.eu
www.cmco.com

BELFAST OFFICE

Unit 1A Ferguson Centre, 57-59 Manse Road
Newtownabbey, BT36 6RW
United Kingdom
Telephone: +44 (0) 2890 840697
Email: sales.ni@cmco.eu
www.columbusmckinnon.ie/ni

COLUMBUS MCKINNON

Columbus McKinnon has a history of over 150 years and is a world leader in lifting and intelligent motion control technology. The innovative portfolio of high-quality brands, including Stahl CraneSystems, Magnetek, Pfaff-silberblau, Duff-Norton, Yale, Dörner, CM and montratec addresses the needs of our customers by enhancing safety and promoting growth and efficiency. Experience, expertise and innovation

combined with a deep understanding of user needs are the formula for success that has long underpinned our portfolio of hoists, material handling equipment and lifting accessories. Columbus McKinnon is a global organization headquartered in Charlotte, USA (North Carolina). Its global presence includes offices and manufacturing facilities in North America, Latin America, Europe, Africa and Asia.



www.cmco.com



www.cmco.com