

Hand pallet truck model HU 25-115 TS SILVERLINE (Tandem rollers)

model HU 25-115 ES SILVERLINE (Single rollers)

Capacity 2500 kg

For the professional transportation of palletised goods and box pallets under demanding conditions.

Features

- Ergonomic safety control handle for one-hand operation of lifting, driving and lowering.
- Ergonomic rubber control handle for safe handling.
- Low maintenance hydraulic pump with hard chromium plated piston.
- Frame and forks in robust steel construction, adjustable connecting rods, especially hardened axles and the high quality powder coating ensure a long life expectancy.



Option: Parking brake

Technical data model HU 25-115 TS SILVERLINE and model HU 25-115 ES SILVERLINE

Model	HU 25-115 TS	HU 25-115 TS	HU 25-115 TS	HU 25-115 TS	HU 25-115 TS	HU 25-115 ES
Art.-No.	034527100	034527101	034527108	034527130	034527184	034527106
Capacity, kg	2500	2500	2500	2500	2500	2500
Load center c, mm	600	600	600	600	600	600
Weight, kg	75	79	79	68	68	84
Tyre type*	VG/PA	VG/PUR	PUR/PUR	PA/PA	PUR/PA	VG/PUR
Steering rollers, mm	200x50	200x50	200x50	200x50	200x50	200x50
Load rollers, mm	82x70	82x70	82x70	80x70	80x70	82x93
Number of wheels/load rollers	2/4	2/4	2/4	2/4	2/4	2/2
Stroke h3, mm	115	115	115	115	115	115
Height of control handle h14, mm	1200	1200	1200	1200	1200	1200
Fork height lowered h13, mm	85	85	85	85	85	85
Overall length L1, mm	1535	1535	1535	1535	1535	1535
Fork height s, mm	45	45	45	45	45	45
Fork width e, mm	160	160	160	160	160	160
Fork length l, mm	1150	1150	1150	1150	1150	1150
Outside dimension of forks b1, mm	540	540	540	540	540	540
Inside dimension of forks b3, mm	220	220	220	220	220	220
Ground clearance m1, mm	40	40	40	40	40	40
Aisle width pallet Ast, mm	1815	1815	1815	1815	1815	1815
Turning circle radius Wa, mm	1330	1330	1330	1330	1330	1330

*PA... Polyamidee, PUR... Polyurethane, VG... Solid rubber