



## Hand stacker model HG

Capacity 300 and 500 kg

Ideal for the occasional, internal application of stacking and transporting of palletised goods.

### Features

- Manual winch for exact positioning of the height.
- Handlebar for easy operation.
- C-profile mast with maintenance free pulley and guide rollers with ball bearings.
- Steering roller with brake for safe parking of the hand stacker.

### Technical data model HG

Model	HG 0315	HG 0515
Art.-No.	034518016	034518017
Capacity, kg	300	500
Load center c, mm	400	600
Wheelbase y, mm	850	1050
Weight, kg	80	90
Tyre type*	PA/PA	PA/PA
Steering rollers, mm	125 x 40	125 x 40
Load rollers, mm	75 x 30	75 x 30
Number of wheels/load rollers	2/2	2/2
Height, mast retracted h <sub>1</sub> , mm	1840	1840
Free lift h <sub>2</sub> , mm	1410	1410
Stroke h <sub>3</sub> , mm	1410	1410
Height, mast extended h <sub>4</sub> , mm	1840	1840
Lifting height max. h <sub>3</sub> + h <sub>13</sub> , mm	1500	1500
Fork height lowered h <sub>13</sub> , mm	90	90
Overall length L <sub>1</sub> , mm	1020	1320
Length incl. apron L <sub>2</sub> , mm	362	362
Overall width B, mm	710	710
Fork height s, mm	50	50
Fork width e, mm	160	160
Fork length l, mm	600	900
Outside dimension of forks b <sub>1</sub> , mm	580	580
Ground clearance m <sub>1</sub> , mm	30	30
Turning circle radius W <sub>a</sub> , mm	855	1155
Lift per one crank rotation with/without load, mm	25	25

\*PA... Polyamide

